

Package: monotone (via r-universe)

October 1, 2026

Type Package
Title Performs Monotone Regression
Version 0.1.2
Author Frank Busing [aut, cre], Juan Claramunt Gonzalez [aut]
Maintainer Frank Busing <busing@fsw.leidenuniv.nl>
Description The monotone package contains a fast up-and-down-blocks implementation for the pool-adjacent-violators algorithm for simple linear ordered monotone regression, including two spin-off functions for unimodal and bivariate monotone regression (see <[doi:10.18637/jss.v102.c01](https://doi.org/10.18637/jss.v102.c01)>).
License GPL-3
Encoding UTF-8
RoxygenNote 7.1.1
NeedsCompilation yes
Repository <https://busingfmta.r-universe.dev>
Date/Publication 2022-05-25 13:00:02 UTC
RemoteUrl <https://github.com/cran/monotone>
RemoteRef HEAD
RemoteSha 36c17fa4b03ac20b8d0a801c9f75ba83b68fe65c

Contents

bimonotone	2
legacy	3
monotone	4
unimonotone	5
Index	7

bimonotone

*Bivariate Monotone Regression Function***Description**

bimonotone performs bivariate monotone regression. The function uses the up-and-down-blocks implementation (Kruskal, 1964) of the pool-adjacent-violators algorithm (Ayer, Brunk, Ewing, Reid, and Silverman, 1955), with additional lookaheads, repeatedly, for both rows and columns, until convergence.

Usage

```
bimonotone(
  x,
  w = matrix(1, nrow(x), ncol(x)),
  maxiter = 65536,
  eps = 1.49011611938477e-08
)
```

Arguments

x	a real-valued matrix.
w	a real-valued matrix with positive weights (default a matrix with ones).
maxiter	maximum number of iterations (default = 65536)
eps	precision of estimates (default = 1.4901161193847656e-08)

Details

Error checking on x, w, maxiter, or eps is not present.

Value

Returns a real-valued matrix with values of both rows and columns of x in monotone order.

References

Bril G, Dykstra R, Pillers C, Robertson T (1984). Algorithm AS 206: isotonic regression in two independent variables. *Journal of the Royal Statistical Society. Series C (Applied Statistics)*, 33(3), 352-357. URL <https://www.jstor.org/stable/pdf/2347723.pdf>.

Busing, F.M.T.A. (2022). Monotone Regression: A Simple and Fast O(n) PAVA Implementation. *Journal of Statistical Software, Code Snippets*, 102 (1), pp. 1-25. (<doi:10.18637/jss.v102.c01>)

Dykstra R.L., Robertson T. (1982). An algorithm for isotonic regression for two or more independent variables. *The Annals of Statistics*, 10(3), 708-716. URL https://projecteuclid.org/download/pdf_1/euclid.aos/11763458

Turner, T.R. (2019). Iso: Functions to Perform Isotonic Regression. R package version 0.0-18. URL <https://cran.r-project.org/package=Iso>

Examples

```
G <- matrix( c( 1, 5.2, 0.1, 0.1, 5, 0, 6, 2, 3, 5.2, 5, 7, 4, 5.5, 6, 6 ), 4, 4 )
print( G )
H <- bimonotone( G )
print( H )
y <- c( 8, 4, 8, 2, 2, 0, 8 )
x <- bimonotone( as.matrix( y ) )
print( x )
x <- bimonotone( t( as.matrix( y ) ) )
print( x )
```

legacy

Monotone Regression Legacy Function

Description

legacy provides some functions for monotone regression from the past. Current implementations have been translated into C for proper comparison in Busing (2022).

Usage

```
legacy(x, w = rep(1, length(x)), number = 0)
```

Arguments

x	a real-valued vector.
w	a real-valued vector with positive weights (default a vector with ones).
number	function number (specifications below).

Details

Legacy implementations by number, function, author, and year:

- 0 = default (do nothing)
- 1 = fitm() by Kruskal (1964).
- 2 = wmrnmh() by van Waning (1976).
- 3 = amalgm() by Cran (1980).
- 4 = pav() by Bril (1984).
- 5 = isoreg() by Gupta (1995).
- 6 = iso_pava() by Turner (1997).
- 7 = isotonic() by Kincaid (2001).
- 8 = isomean() by Strimmer (2008).
- 9 = pooled_pava() by Pedregosa (2011).

- 10 = linear_pava() by Tulloch (2014).
- 11 = inplace_pava() by Varoquaux (2016).
- 12 = md_pava() by Danish (2016).
- 13 = reg_1d_l2() by Xu (2017).
- 14 = jbkpava() by de Leeuw (2017).

Error checking on w or x is not present.

Value

Returns a real-valued vector with values of x in increasing order.

References

Busing, F.M.T.A. (2022). Monotone Regression: A Simple and Fast O(n) PAVA Implementation. *Journal of Statistical Software, Code Snippets*, 102 (1), pp. 1-25. (<doi:10.18637/jss.v102.c01>)

Examples

```
y <- c( 8, 4, 8, 2, 2, 0, 8 )
x <- legacy( y, number = 1 )
print( x )
```

monotone

Monotone Regression Function

Description

monotone performs simple linear ordered monotone or isotonic regression. The function follows the up-and-down-blocks implementation (Kruskal, 1964) of the pool-adjacent-violators algorithm (Ayer, Brunk, Ewing, Reid, and Silverman, 1955) with additional lookaheads (Busing, 2022).

Usage

```
monotone(x, w = rep(1, length(x)))
```

Arguments

x a real-valued vector.

w a real-valued vector with positive weights (default a vector with ones).

Details

Error checking on x or w is not present.

Value

Returns a real-valued vector with values of x in increasing order.

References

- Ayer M., H.D. Brunk, G.M. Ewing, W.T. Reid, and E. Silverman (1955). An empirical distribution function for sampling with incomplete information. *The Annals of Mathematical Statistics*, pp. 641-647. URL <https://www.jstor.org/stable/pdf/2236377.pdf>.
- Busing, F.M.T.A. (2022). Monotone Regression: A Simple and Fast $O(n)$ PAVA Implementation. *Journal of Statistical Software, Code Snippets*, 102 (1), pp. 1-25. (<doi:10.18637/jss.v102.c01>)
- Kruskal, J.B. (1964). Nonmetric multidimensional scaling: a numerical method. *Psychometrika*, 29(2), pp. 115-129. URL http://cda.psych.uiuc.edu/psychometrika_highly_cited_articles/kruskal_1964b.pdf.

Examples

```
y <- c( 8, 4, 8, 2, 2, 0, 8 )
x <- monotone( y )
print( x )
```

unimonotone

Unimodal Monotone Regression Function

Description

unimonotone performs unimodal monotone regression. The function follows the up-and-down-blocks implementation (Kruskal, 1964) of the pool-adjacent-violators algorithm (Ayer, Brunk, Ewing, Reid, and Silverman, 1955) for both isotonic and antitonic regression, and the prefix isotonic regression approach (Stout, 2008) with additional lookaheads and progressive error sum-of-squares computation.

Usage

```
unimonotone(x, w = rep(1, length(x)))
```

Arguments

- | | |
|-----|--|
| x | a real-valued vector. |
| w | a real-valued vector with positive weights (default a vector with ones). |

Details

Error checking on x or w is not present.

Value

Returns a real-valued vector with values of x in umbrella order.

References

- Bril G, Dykstra R, Pillers C, Robertson T (1984). Algorithm AS 206: isotonic regression in two independent variables. *Journal of the Royal Statistical Society. Series C (Applied Statistics)*, 33(3), 352-357. URL <https://www.jstor.org/stable/pdf/2347723.pdf>.
- Busing, F.M.T.A. (2022). Monotone Regression: A Simple and Fast $O(n)$ PAVA Implementation. *Journal of Statistical Software, Code Snippets*, 102 (1), pp. 1-25. (<doi:10.18637/jss.v102.c01>)
- Stout, Q.F. (2008). Unimodal Regression via Prefix Isotonic Regression. *Computational Statistics and Data Analysis*, 53, pp. 289-297. URL <https://doi.org/10.1016/j.csda.2008.08.005>
- Turner, T.R. and Wollan, P.C. (1997). Locating a maximum using isotonic regression. *Computational statistics and data analysis*, 25(3), pp. 305-320. URL [https://doi.org/10.1016/S0167-9473\(97\)00009-1](https://doi.org/10.1016/S0167-9473(97)00009-1)
- Turner, T.R. (2019). Iso: Functions to Perform Isotonic Regression. R package version 0.0-18. URL <https://cran.r-project.org/package=Iso>

Examples

```
y <- c( 0.0, 61.9, 183.3, 173.7, 250.6, 238.1, 292.6, 293.8, 268.0, 285.9, 258.8,
297.4, 217.3, 226.4, 170.1, 74.2, 59.8, 4.1, 6.1 )
x <- unimonotone( y )
print( x )
```

Index

bimonotone, [2](#)

legacy, [3](#)

monotone, [4](#)

unimonotone, [5](#)